

Standard - Drehmomente nach DIN

Standardprofil (Drehmoment in NM-Reference: DIN899)						Innensechskant		TORX-Profil	
SW	1/4"	3/8"	1/2"	3/4"	1"	SW	NM	SW	NM
M 4	10,4					H 0,7	0,08	T6	0,9
M 4,5	12,6					H 0,9	0,18	T7	1,7
M 5	15,1					H 1,3	0,53	T8	2,6
M 5,5	17,8					H 1,5	0,82	T9	3,4
M 6	20,6					H 2	1,9	T10	4,52
M 7	26,8	33,2				H 2,5	3,8	T15	7,68
M 8	33,6	45,5	94,1			H 3	6,6	T20	12,7
M 9	41,1	59,9	119,2			H 4	16	T25	19
M 10	49,1	76,7	147,0			H 5	30	T27	26,9
M 11	57,8	96,0	178,0			H 6	52	T30	37,4
M 12	67,0	118,0	212,0			H 7	80	T40	65,1
M 13	68,6	141,0	249,0			H 8	120	T45	103,5
M 14	68,6	169,0	288,0			H 10	220	T50	158,7
M 15		198,0	331,0			H 12	370	T55	256,7
M 16		225,0	377,0			H 14	590	T60	445,4
M 17		225,0	425,0			H 17	980	T70	700,8
M 18		225,0	477,0			H 19	1360	T80	1048
M 19		225,0	531,0			H 22	2110		
M 20		225,0	569,0			H 24	2750		Reference : CAMCAR
M 21		225,0	569,0			H 27	3910		
M 22		225,0	569,0	569,0		H 32	4000		
M 23			569,0	569,0		H 36	4000		
M 24			569,0	569,0			Reference :DIN-ISO2936		
M 25			569,0	583,0					
M 26			569,0	624,0					
M 27			569,0	665,0					
M 28			569,0	707,0					
M 30			569,0	795,0					
M 32			569,0	888,0					
M 34			569,0	984,0					
M 36				1084,0					
M 41				1353,0					
M 46				1569,0	2143,0				
M 50				1569,0	2329,0				
M 55				1569,0	2562,0				
M 60				1569,0	2795,0				
M 65					2795,0				
M 70					2795,0				
M 75					2795,0				
M 80					2795,0				
Vierkant									
T-Griff	Reference :DIN 3122 (N.M)								
T-HANDLE SLIDING	1/4"Dr.	3/8"Dr.	1/2"Dr.	3/4"Dr.	1"Dr.				
	55	180	455	1255	2236				
Knarren	Reference :DIN 3122 (N.M)								
Ratchet Handle	1/4"Dr.	3/8"Dr.	1/2"Dr.	3/4"Dr.	1"Dr.				
	62	202	512	1412	2515				
Gelenkhebel	Reference :DIN 3122 (N.M)								
Flexible Handle	1/4"Dr.	3/8"Dr.	1/2"Dr.	3/4"Dr.	1"Dr.				
	62	202	512	N/A	N/A				
Verlängerung	Reference : DIN 3123 (N.M)								
EXT. BAR	1/4"Dr.	3/8"Dr.	1/2"Dr.	3/4"Dr.	1"Dr.				
	62	202	512	1412	2515				
Universalgelenk	Reference: DIN 3123 (N.M)								
Universal Joint	1/4"Dr.	3/8"Dr.	1/2"Dr.	3/4"Dr.	1"Dr.				
	34	112	284	784	N/A				

N/A: DIN